

XPC SV25



Form Factor

Shuttle Form Factor

CPU Support

Intel Pentium III/Celeron and VIA Cyrix III/C3 in sock370 with 66/100/133MHz FSB

Chipsets

VIA VT8606T/686B

Memory

2 x 168 pin Socket support PC100/133 SDRAM up to 512MB

VGA

Build in VIA Savage4 high performance 2D/3D engine

TV-Out

Support NTSC and PAL format in S-Video/Composite terminal

Audio

VIA AC97 audio

IDE interface

2 x UltraDMA/100 IDE channels

IEEE 1394a

VIA VT6306, complies with 1394 OHCI specification revision 1.0 support up to 400Mb/s data transfer rate

Ethernet

Realtek 8100B support IEEE 802.3u 10/100Base-T
Supports Wake-On-LAN function

Expansion Slot

1 x PCI slot

On board connectors and Headers

1 x PS/2 Keyboard	1 x PS/2 Mouse
1 x VGA port	1 x Serial Port
1 x Parallel port	2 x 1394 ports
1 x S-Video connector	1 x Composite connector
2 x USB ports	1 x RJ45 port
1 x line-in connector	1 x line-out connector
2 x fan connectors	2 x Front Panel USB Connector
1 x ATX power connector	

Chassis

Shuttle C type

Dimension

270(L)x190(W)x170(H)mm, 2.40Kg (N.W.), 3.55Kg (G.W.)

Material

Aluminum alloy

Extension Bay

2 x 3.5" bays 1 x 5.25" bay

Front Panel

2 x USB ports	1 x Mic-In
1 x Speaker-Out	1 x Power-On button
1 x Reset button	

Back Panel

1 x PCI slot	1 x PS/2 Keyboard
1 x PS/2 Mouse	1 x VGA port
1 x Serial Port	2 x 1394 ports
2 x USB ports	1 x RJ45 port

Power

Dimension:	82(W) x 43(H) x 190(D) mm (Max)
Input:	110 / 230V AC
Output:	150W
EMI Certified:	FCC, CE, BSMI
Safety Certified:	UL, TUV, CB
Power Cord:	Depends on specific region demand

Accessories

- 1 x Rise for PCI expansion
- 1 x Mainboard User manual
- 1 x Mainboard CD-Driver
- 1 x XPC Installation Guide
- 1 x FDD Cable
- 1 x HDD Cable
- 1 x CD-ROM Cable
- 1 x Power cord
- Screws
- Twin Adhesive
- Friendly Front Feet