

X_{PC} SS50C



Form Factor

Shuttle Form Factor

CPU Support

Intel Pentium 4/Celeron in 478-pin package with 400MHz FSB

Chipsets

SiS650/961

Memory

2 x 184 pin Socket support DDR200/266 unbuffer DDR SDRAM up to 2GB

VGA

Build in SiS315 high performance 256-bit 3D engine

TV-Out

SiS301 support NTSC and PAL format in S-Video/Composite ports

Audio

Cmedia 8738 supports 5.1 channel audio
Support Digital SPDIF In/Out

IDE interface

2 x UltraDMA/100 IDE channels

IEEE 1394a

Lucent FW323, complies with 1394 OHCI specification revision 1.0 support up to 400Mb/s data transfer rate

Ethernet

Realtek 8100B support IEEE 802.3u 10/100Base-T
Supports Wake-On-LAN function

Expansion Slot

2 x PCI slots

On board connectors and Headers

3 x fan connectors
1 x ATX main power connector
1 x Peripheral power connector
2 sets of 2x5 pin USB2.0 headers
1 set of 2x5 pin Front Panel IEEE1394a header
1 set of Parallel header
CD_In header
Mic_In header
Speaker_Out header
SPDIF_Out header

Chassis

Shuttle C type

Dimension

280(L)x200(W)x180(H)mm, 2.70Kg (N.W.), 4.20Kg (G.W.)

Material

Aluminum

Extension Bay

2 x 3.5" bays 1 x 5.25" bay

Front Panel

2 x USB ports 1 x 1394 port
1 x Mic-In 1 x Speaker-Out
1 x Power-On button 1 x Reset button

Back Panel

2 x PCI slots 1 x PS/2 Keyboard
1 x PS/2 Mouse 1 x VGA port
2 x Serial ports 2 x 1394 ports
2 x USB ports 1 x RJ45 port
1 x Front out connector 1 x Rear out connector
1 x Center/Bass port 1 x S-video/composite port

Power

Dimension: 82(W) x 43(H) x 190(D) mm (Max)
Input: 110 / 230V AC
Output: 160W/150W(PFC)
EMI Certified: FCC, CE, BSMI
Safty Certified: UL, TUV, CB
Power Cord: Depends on specific region demand

Accessories

1 x Mainboard User manual
1 x Mainboard CD-Driver
1 x XPC Installation Guide
1 x FDD Cable
1 x HDD Cable
1 x CD-ROM Cable
1 x 7pin Mini DIN to RCA Cable
1 x Power cord
Screws
Twin Adhesive